


Declaration Of Performance

1. Reference No: PP32-Plastisol

2. Product type: PP32 (S220GD)



Intended use: Self-supporting, trapezoidal profile for roofs and walls

4. Manufacturer: Metal Roofing & Cladding Limited. Stourprt Road, Kidderminster, Worcestershire. DY11 7QL.

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V

System 3	System 4
Products are conducted though initial inspection and are subject to production audits according to EN 14782:2006	System 4 has been used for constancy of other characteristics

6. Harmonised standard EN 14782

7. Declared Performance

Main Characteristic	Performance	Harmonised Technical Specifications
Resistance to concentrated force	NPD	EN 14782:2006, Section 4.3
Material thickness	0.4-0.7mm Plastisol coated galvanised steel	EN 14782:2006, Section 4.8
Dimensional tolerances	NPD	EN 14782:2006
Water permeability	Impermeable in the absence of holes Visual inspection passed	EN 14782:2006, Section 4.4
Dimensional changes	Thermal expansion coefficient: steel $12 \times 10^{-6} \text{ K}^{-1}$	EN 14782:2006, Section 4.6
Release of hazardous substances	NPD	EN 14782:2006, Section 4.11
External fire performance	Class B _{roof} (t1), class B _{roof} (t2), class B _{roof} (t3)	EN 14782:2006, Section 4.9
Reaction to fire	C-s2,d0	EN 14782:2006, Section 4.10
Durability	NPD	EN 14782:2006, Section 4.3 and 4.8

8. The performance of the product according to the number 1 and 2 corresponds to the declared performance of number 7. The manufacturer according to point 4 is alone responsible for the issue of this declaration of performance. Signed on behalf of and in the name of the manufacturer by:



Tom Parkes
General Manager

Kidderminster, England, 26/10/2024